



1

P.O. Drawer 507 • Leeds, Alabama 35094 • Phone (205) 640-5181 • Fax (205) 640-1147 • Email: sales@precisionhusky.com

## PRECISION SAWMILL SERIES ROTARY KNIFE GRINDER

Precision Rotary Knife Grinder's anti-friction bearings with continuous circular grinding eliminates the reversal vibration shock commonly experienced in reciprocating grinders. Any size knife can be ground from 3/16" to 1-1/4" [5mm to 32mm] thick and knife widths from 2" to 6" [51mm to 152mm]. Accommodates knives from 5" to 28" [127mm to 711mm] long. The low height of this compact grinder makes loading and unloading knives easier. Precision's Rotary Knife Grinder is complete, ready to use with diamond wheel dresser, bevel gauge for setting fixtures, coolant pump and tank, and all motors and starters.



All controls are housed in a NEMA #12 water-tight control box. The operational controls are mounted on the side of the control panel for additional safety. An electrical lock out utilizing a key prohibits any motor function during loading or maintenance.

## STANDARD EQUIPMENT:

- 5 HP [3.72kw] grinding wheel, totally enclosed, fan cooled, (TEFC) motor, 3 phase, 60 cycle, 220/440 volt. Single phase available as an option.
- 3/4 HP [0.5kw] motor for driving table.
- Diamond wheel dresser.
- Bevel gauge for setting fixtures.
- 3-Knife fixtures will accommodate up to three 28" [711mm] knives.
- 4-Knife fixtures will accommodate up to four 23" [584mm] knives.
- 6-Knife fixtures will accommodate up to six 21-1/2" [546mm] knives.
- Knife width maximum 5" [127mm].

Specifications given were approved at the time of initial printing and are subject to change without notice and without incurring any liability.

Sales and Service



## www.precjajonnakh.com